

ABSTRACT OF THE DISCLOSURE

An ATM dual system wherein the intervals between couplers and ONUs are dualized comprises a dualized line termination device loading a PLOAM cell transmitter/receiver within an OLT, the PLOAM
 5 cells being used for monitoring and being transmitted and received between the OLT and the ONU, and a PST message transmitter/receiver which loads and allocates switch controlling information to K1/K2 byte areas of the aforementioned PLOAM cells, and a VP/VC switch which
 10 switches each of the relevant VP or VC on the basis of the aforementioned K1/K2 byte information.

(1)
 (2)
 (3)
 (4)
 (5)
 (6)
 (7)
 (8)
 (9)
 (10)
 (11)
 (12)
 (13)
 (14)
 (15)
 (16)
 (17)
 (18)
 (19)
 (20)
 (21)
 (22)
 (23)
 (24)
 (25)
 (26)
 (27)
 (28)
 (29)
 (30)
 (31)
 (32)
 (33)
 (34)
 (35)
 (36)
 (37)
 (38)
 (39)
 (40)
 (41)
 (42)
 (43)
 (44)
 (45)
 (46)
 (47)
 (48)
 (49)
 (50)
 (51)
 (52)
 (53)
 (54)
 (55)
 (56)
 (57)
 (58)
 (59)
 (60)
 (61)
 (62)
 (63)
 (64)
 (65)
 (66)
 (67)
 (68)
 (69)
 (70)
 (71)
 (72)
 (73)
 (74)
 (75)
 (76)
 (77)
 (78)
 (79)
 (80)
 (81)
 (82)
 (83)
 (84)
 (85)
 (86)
 (87)
 (88)
 (89)
 (90)
 (91)
 (92)
 (93)
 (94)
 (95)
 (96)
 (97)
 (98)
 (99)
 (100)